


## Alkūnē 90° virinama - plieninē (juoda)



**Standartas:** EN 10253-1 (DIN 2605)

**Medžiaga:** P235TR2 - S235 (R.St.37.0)

Kodas	DN	DN (inch)	DN (mm)	S (mm)	R (mm)	B (mm)	kg
704213000	15	1/2"	21,3	2	29	38	0,04
700269000	20	3/4"	26,9	2,3	29	43	0,08
700337000	25	1"	33,7	2,6	38	56	0,11
700424000	32	1 1/4"	42,4	2,6	48	70	0,18
700483000	40	1 1/2"	48,3	2,6	57	83	0,26
700603000	50	2"	60,3	2,9	76	106	0,48
700761000	65	2" 1/2	76,1	2,9	95	132	0,73
700889000	80	3"	88,9	3,2	114	159	1,16
700114000	100	4"	114,3	3,2	152	210	2,37

### Matmeņu tolerancijas:

$D = \pm 1\% D \text{ MIN } \pm 0,5 \text{ mm}$

$S = S \leq 4 \text{ mm } (-12,5\% \times S / +20\% \times S) \quad S > 4 \text{ mm } (-12,5\% \times S / +15\% \times S)$

$R = \pm 2 \text{ mm } \leq \text{DN } 200 \pm 3 \text{ mm DN } 250 - 300$

$B = \pm 7 \text{ mm}$